Full-Color Giclée Panels Specifications

Part I - General

1.1 Scope

A. Furnish plaques and hardware necessary to install Full-Color Giclée panel plaques, shown on drawings and herein specified.

1.2 Submittals

A. Manufacturer's illustrated product literature and specifications.

B. Installation instructions

1.3 Quality Assurance

A. Manufacturer to have a minimum of 10 years experience in manufacturing Giclée panels.

B. All Giclée panels to be manufactured by one manufacturer.

Part II - Products

2.1 Acceptable Manufacturer or Manufacturer's Representative

A. Spike's Signs 2701 Grant Avenue Philadelphia, PA 19114

Phone: 215-574-8100 or 800-333-2927

Fax: 215-574-8113 Email: sales@GoSpikes.com Web: www.GoSpikes.com

2.2 Materials

A. Bronze (220 Commercial)

B. Aluminum (#5052)

C. Brass (C46400)

D. Stainless Steel (304 or 316 Alloy)

E. Lexan

2.3 Process

- 1. Sizes: Aluminum or Stainless Steel sizes up to 48"x96", Bronze or Brass up to 36"x60", Lexan up to 48"x96".
- 2. Gauge: 1/8"thick standard. Optional 1/16", 1/4", 5/16"th.
- Shape: Rectangle, square or custom shapes per art.
- Background: Optional exposed metal, primed, painted or printed per art.
- Returns: Painted or brushed panel returns.
- Giclée plaques are high quality, printed reproductions of art (1200 dpi), using UV stable ink. Good for interiorexterior use.
- Clearcoat: printed panels are sprayed with 2-part hardened semi-gloss acrylic polyurethane, then baked. Optional matte or gloss.

2.4 Mounting Hardware

A. Hardware and instructions are provided for several mounting methods, including Blind Mount, Double-Face Tape, Solid Wall Mount, Hollow Wall Mount, Wood Wall Mount - with machine or wood screws.

Part III - Execution

3.1 Installation

 A. A qualified installer shall install Giclée panels. Additional structural support may be required for larger/heavier panels.

3.2 Warranty

A. Giclée panels used in interior applications shall be guaranteed for the life of the original installation. Exterior installs-10 years.

3.3 Maintenance

A. Cleaning of panels as needed, per manufacturer's recommendations.